

Activity 3.2.2 Fluid Power Practice Problems

Directions

Answer the following questions. Sketch each, then label all known values. Be sure to include all steps and units throughout each solution.

All problems assume that conditions are ideal. Forces such as friction are not considered.

Problems

A pneumatic system is producing 100 lb/in.² of gauge pressure. A cylinder is needed to press an adhesive label onto a product. It has been determined that 5 lb of force is optimal to complete this task.

1. Sketch and label all known and unknown values.

1. Cheton and laber an known and unknown values.			
Sketch			
2. What is the requ	uired area of the pneumatic cylinder?		
Formula	Substitute / Solve	Final Answer	
3. What is the requ	uired diameter of the pneumatic cylinder?		
Formula	Substitute / Solve	Final Answer	

A hydraulic lift system utilizes two 3 in. diameter cylinders. Workers must determine how much the system is capable of lifting before deciding how much weight can be lifted safely. The system runs at a gauge pressure of 2000 lb/in.². 4. Sketch and label all known and unknown values. Sketch 5. What is the area of each piston? Formula Substitute / Solve Final Answer 6. How much is the system capable of lifting? Formula Substitute / Solve Final Answer The gauge pressure of a pneumatic cylinder reads 20 lb/in.² when the volume is 30 in.3. The cylinder is compressed until the gauge reads 60 lb/in.2. Assume standard atmospheric pressure (14.7 psi). 7. Sketch and label all known and unknown values. Sketch 8. What is the absolute pressure before and after the cylinder gas is compressed? Formula Substitute / Solve Final Answer

© 2024 Project Lead The Way, Inc.

	ume in the cylinder after the gas is compres	35Cu:		
Formula	Substitute / Solve	Final Answer		
	. 00: 3 (
	re in a 28 in. ³ container with a free sliding pages. The temperature is raised to 200 °F. Wh			
10.Sketch and lab	el all known and unknown values.			
Sketch				
11. What are the absolute temperature readings initially and after the temperature has been raised?				
Formula	Substitute / Solve	Final Answer		
Formula	Substitute / Solve	Final Answer		
12. What is the volume in the cylinder after the temperature has been raised?				
Formula	Substitute / Solve	Final Answer		

A 60 ft ³ compressor tank container has a gauge pressure of 160 lb/in. ² and a	
temperature of 70 °F. The temperature after some time decreases to 40 °F.	Find
the final pressure in the tank. Assume standard atmospheric pressure.	

13. Sketch and label all known and unknown values. Sketch 14. What are the absolute temperature readings initially and after the temperature decreases? Formula Substitute / Solve Final Answer Formula Final Answer Substitute / Solve 15. What is the absolute pressure of the system before the temperature decreases? Formula Substitute / Solve Final Answer 16. What is the absolute pressure of the system after the temperature decreases? Formula Substitute / Solve Final Answer

A flow meter is attached in a hydraulic line that measures 12 gal/min. The line has an inside diameter of 1.5 in. Find the flow velocity where the fluid passes the meter.				
17. Sketch and label all known and unknown values.				
	Sketch			
18. What is the flow rate measured as in. ³ /min at the meter?				
Formula	Substitute / Solve	Final Answer		
	a of inside diameter of the line?	E. 14		
Formula	Substitute / Solve	Final Answer		
20. What is the flow	velocity where the fluid passes the meter?			
Formula	Substitute / Solve	Final Answer		
A hydraulic press must be used to press-fit two components together in an assembly process. The system must generate at least 775 lb of force to perform the press fit. The piston at the input cylinder is pushed with a force of 250 lb and has an area of 30 in. ² . The output can use up to 15 cylinders that are each 30 in. ² . How many cylinders are needed? 21. Sketch and label all known and unknown values.				
Sketch				

ZZ. FIOW MUCH MEC	chanical advantage is required to gain the r	iccessary folde!
Formula	Substitute / Solve	Final Answer
23. How many outp	out cylinders must be incorporated into the	design?
Formula	Substitute / Solve	Final Answer
24. How much oil fl	ow will a 2.50-cubic-inch pump produce op	perating at 1100 rpm?
Formula	Substitute / Solve	Final Answer
25. A hydraulic sys	tem has a flow rate of 12 gpm and operate	s at 1600 psi. Determine
the horsepower	the system needs to lift a 15,000-lb force.	·
Formula	Substitute / Solve	Final Answer
Conclusion		
	rs use the knowledge acquired from fluid po	ower equations
	e related career paths and explain why und	<u>-</u>
research the	e relateu career patris and explain why und	aerstanding nulu powe

is essential to each one.